

GROUND LEVELLING

- Extremely tough and rugged
- Heavy cylinders
- Pneumatic floating wheels for high adaptability to the ground
- Coupling to the machine

GRADER BLADE



- On/off distributor
- ST52 steel structure
- Manual flow regulator
- Electrical control kit



DUAL GRADER BLADE



- Proportional and on/off distributor
- It works both as a grader blade and as a tilt dozer blade
- Double bevel curved blade
- Over center valve on wheel lifting cylinder




Control box





CATALOGUE

GROUND LEVELLING



DIMENSIONS

GR 220/270

A	Width	2200/2700
B	Depth	2500
C	Height	1900

The Grader Blade M3 Model Dual can be fitted to small skid steer loaders with power ranging from 50 to 120 HP. IT is ideal for the preparation and the leveling of lands, roads and yards.

It is equipped with a hydraulic control panel of the 26° inclination system, of the oscillation at 15°, of the blade height adjustment $\pm 150\text{mm}$, of the lifting of the front wheels, a distributor on / off, blade extensions, coupling to the machine, hydraulic hoses and electric control kit.

OPTIONALS

Wifi laser control system
(transmitter not included)

Wired laser system with control box
(transmitter not included)(1)

Left/right closing plate (2)



MODEL	GR 220/270
Blade width [mm]	2200/2700
Weight [kg]	850
Hydraulic blade inclination R/L	$\pm 26^\circ$
Hydraulic blade oscillation R/L	$\pm 15^\circ$
Blade height [mm]	540

