



DIMENSIONS

| | | SA 150 | SA 180 | SA 210 | SA 240 |
|---|---------------|--------|--------|--------|--------|
| A | Width | 1770 | 2070 | 2270 | 2670 |
| B | Depth | 1620 | 1620 | 1620 | 1620 |
| C | Height | 650 | 650 | 650 | 650 |

- Coupling for skid steer loaders
- Direct drive hydraulic motor

The angle broom sweeper M3 fits any kind of skid steer loaders, backhoe and wheel loaders and telehandlers (up to 80 HP). Thanks to its strong structure it can be used for the cleaning of construction yards, streets, large courtyard areas or as a snow blade, in case of light snowfalls.

It is equipped with hydraulic motor with direct transmission, hydraulic hoses complete with quick couplings (only on SSL), +/-30° mechanical adjustment of the work angle, PPN brush Ø 550 mm, no. 2 support wheels Ø 200x50 mm and SSL coupling.

OPTIONALS

| | | |
|--|----------------------------------|--|
| | Floating Coupling with 3rd wheel | Hydraulic Angling complete with valve and cylinder |
| Sprinkler kit with 100 L Tank, electric pump and hoses with nebulizers | 3rd wheel Ø 200x50 mm | |



| MODEL | SA 150 | SA 180 | SA 210 | SA 240 |
|-----------------------------------|---------|----------------|---------|---------|
| Working width [mm] | 1500 | 1800 | 2100 | 2400 |
| Working width with 30° angle [mm] | 1299 | 1566 | 1736 | 2078 |
| Min/max flow rate [L/min] | 25/100 | 25/100 | 25/100 | 25/100 |
| Min/max pressure [bar] | 100/250 | 100/250 | 100/250 | 100/250 |
| Ø Brush [mm] | 550 | 550 | 550 | 550 |
| Number of rollers [n°] | 2x750 | 1x800 - 1x1000 | 2x1000 | 2x1170 |
| Weight [kg] * | 295 | 310 | 380 | 416 |

* The value indicated in the table refers to the weight of the sweeper with universal coupling for skid loaders

